



NCCF/JPR/TENDER/2025-26/ 139

Date:09.04.2026

SHORT TENDER NOTICE

Introduction

National Cooperative Consumers' Federation of India Ltd. (NCCF), Jaipur Branch, invites sealed tenders from empaneled and qualified business associates for supply of various furniture at Sawai Man Singh Medical college and attached hospitals (SMS), Jaipur. As per the attached specification, in accordance with General Financial Rules (GFR), 2017 and other applicable rules.

1. NCCF Jaipur reserves the right to reject all or any of the applications submitted in response to this tender at any stage without assigning any reasons whatsoever.
2. NCCF Jaipur reserves the right to modify, cancel, suspend, change or supplement this Tender at any stage.
3. Any change to this tender document shall be uploaded on NCCF website <https://nccf-india.com/> applicants are advised to keep viewing the NCCF website for any corrigendum/change.

Scope of work

The successful vendor shall be responsible for the supply of various furniture at Sawai Man Singh Medical college and attached hospitals (SMS), Jaipur as per the specifications sheet attached.

The scope of work involves Supply and installation of various furniture at Sawai Man Singh Medical college and attached hospitals (SMS), Jaipur conforming strictly to the specification, quality standards and quantities prescribed.

This tender is issued by NCCF for selection of eligible and qualified vendors for supply of various furniture as per specifications and requirements of SMS medical college and attached hospitals, Jaipur.

Handwritten signature

Technical specifications:-

As per Annexure – IV

Technical Bid:-

S.No.	Information	Details
1.	Name of Work	Supply of various furniture at Sawai Man Singh Medical college and attached hospitals (SMS), Jaipur
2.	Period of Work	Supply the goods within 60 days.
3.	Last date of submission of Tender	15/04/2026 at 05:00 PM
4.	Tender opening Date	15/04/2026 at 06:00 PM
5.	Place of submission of Tender/ Opening of Tender	Office of NCCF, 3rd Floor, Western Wing, Nehru Sahakar Bhawan, Bhawani Singh Marg, Jaipur-302001
6.	Bid System	Two Bid system 1. Technical Bid 2. Financial Bid
7.	Earnest Money Deposit (EMD)	Rs. 1,00,000.00 (Rs. One Lakh only through RTGS or DD. Unsuccessful bidder will be returned EMD within 7 days of finalisation of the bid. MSE vendors will be exempted from depositing EMD (Valid proof need to be submitted claiming the exemption)
8.	Bank Details / Account Details	Name of Account Holder: - NCCF of India ltd. Account Number: - 1331011113 Name of Bank and Branch: - Central Bank of India, Sansar Chandra Road, Jaipur IFSC Code: - CBIN0281065
9.	GST registration certificate	
10.	PAN Card	
11.	GST return (GSTR-3B) last 3 months	
12.	Turnover certificate Last 3 years	
13.	ITR for last 3 years	
14.	Notarized affidavit on Rs.100 NJS in original for non-engagement in fraudulent corrupt practice, non-blacklisting in any Govt. organisation.	

Handwritten signature

Terms and conditions:-

1. Selection of the bidder will be made on the basis of maximum margin offered for NCCF and lowest rate quoted.
2. NCCF Shall be at liberty to distribute 40% of the total tendered quantity of materials amongst other than L1 bidders subject to acceptance of L1 rates by other than L1 bidders and fulfillment of eligibility criteria by them. The Distribution is solely the discretion of NCCF.
3. NCCF shall terminate the empanelment of a Business Associate if they have competed against NCCF in any bid either individually, as a partner or in a Joint Venture.
4. EMD of unsuccessful tender will be refunded only after finalization of the bid. No interest will be paid on it.
5. Tender Forms - envelope - A Technical Bid and envelope - B shall be submitted in separate sealed envelope.
6. First preference shall be given to the empaneled Business Associate of Tendering Branch of NCCF. Second preference (in case of absence of valid Business Associate of tendering Branch) shall be given to Empaneled Business Associate of other NCCF Branches.
7. The payment shall be made only after payment being received by NCCF from the concerned department. This is a mandatory and non-negotiable condition.
8. Supply must be completed within the stipulated period. Delay will attract liquidated damages and plenty.
9. Any rejection at inspection or non-conformance to technical specifications will be replaced by the vendor within 15 days at their own cost.
10. The vendor shall not sub-contract, assign, or transfer the supply order in whole or part, without written consent of NCCF.
11. The vendor shall indemnify NCCF against any financial, legal, or reputational loss arising out of non-compliance with the conditions of the buyer department.
12. NCCF reserves the right to postpone/cancel the tender and accept or reject any bid without assigning any reason.

Bid Submission Instructions:-

1. Bid shall be submitted physical on or before 15/04/2026 at 5:00 PM
2. Bids received after specified date and time shall be rejected.



3. Late bids shall not be considered under any circumstances.
4. Bidder shall ensure all documents are clear, legible, and properly arranged.
5. Incomplete bids or bids without Bid Security shall be treated as invalid.
6. All pages of tender documents shall be initialed by authorized signatory.
7. Tender documents should bear seal / stamp of firm / organization.
8. Bids with interlineations or alterations should bear initials of authorized signatory.
9. Tender without EMD, shall not be accepted except in case of valid exemption sought by the bidder.
10. EMD deposited by the successful bidder may also be treated / considered as security deposit.
11. Such a security deposit shall be refunded interest free after successful execution of the order.
12. If the supplier fails to supply the quantity as per Order & Tender conditions, the security deposit shall be liable to be forfeited and the supplier will be blacklisted.
13. All the data, record, etc should be maintained with confidentiality. There should be no breach of obligation on the part of firm.. In case of breach of obligation, appropriate action will be taken against the party.
14. The supplier shall not sublet the work to any third party without written consent of the NCCF.
- 15 At any stage, if it is found that the business associate / proprietor, etc has given incorrect and misleading certificate / information / document(s). NCCF shall free to take suitable action including cancellation of contract, blacklisting of the applicant, etc.
16. Quantity of the items may vary depending upon the requirement.
17. In case of any ambiguity/ dispute in the interpretation of any of the clauses in this tender document, NCCF's interpretation of the clauses shall be final and binding on all applicants/parties.

Bid Validity and Responsiveness:

1. The bidder quoting the lowest rate (L1) will be awarded the tendered quantity as per the terms and conditions of this tender.
2. Only technically complaint bids will be considered for price evaluation.
3. Bid shall remain valid for minimum 180 days from bid opening date

Arshad

4. Bids not meeting technical and mandatory requirements shall be treated as non-responsive and rejected
5. Procuring authority shall not waive responsiveness requirements
6. Deviation from tender specifications shall result in bid rejection

Eligibility Criteria:

1. Only empanelled business associated with NCCF can participate, subject to fulfillment of eligibility and evaluation criteria.
2. Be a legally registered entity (Proprietorship/Partnership/LLP/Company/Cooperative).
3. Have minimum 03 years of experience in supply/manufacture of various furniture or similar items any Central Government/State Govt./Autonomous Bodies/PSU/any other Central/State Govt. agencies, etc.
4. Turnover certificate issued by chartered accountant duly sealed and signed with UDIN.
5. The annual average turnover for last 3 years should be minimum of Rs 3.00 cr (Issued by Chartered Accountant with valid UDIN).
6. Valid GST, PAN, and statutory registrations are mandatory.
7. Vendor must not be blacklisted/debarred by any Government/PSU/Autonomous body, etc (affidavit required).
8. Vendor shall not be under a declaration of ineligibility for corrupt and fraudulent practices issued by the any Government Organization.
9. The vendor must submit all the relevant and material documents in support of their eligibility.

Earnest Money Deposit (EMD):-

- Amount Rs. 1,00,000.00 (Rupees One lakh only)
- Mode: DD/Online transfer/Bank Guarantee in favour of National cooperative Consumers Federation of India Ltd
- EMD exemption, if any shall be as per GFR, 2017 Rule and applicable Government Rule.

Security Deposit / Performance Security:-

- Successful bidder shall submit Performance Security @ 2% of contract value (as decided by NCCF) within 7 days of placement of order. The validity will be up to completion of



contract including warranty period. NCCF reserves the right to forfeit performance security in case of termination, breach of terms and conditions, non-compliance of instruction issues from NCCF time to time, etc. MSME vendors need to submit performance of 0.5% of the contract value.

Price & Financial Terms:-

- Prices must be firm and inclusive of all taxes, duties, freight, insurance, packing, and forwarding, unless specified otherwise.
- GST shall be quoted separately as applicable.
- No escalation in price shall be allowed during the contract period.

Payment Terms:-

- 1) Payment shall be released to the successful vendor only after NCCF receives the corresponding payment from the concerned client department for the respective quantity supplied. NCCF will not be liable to make any payment if not received from the department for any reason whatsoever.
- 2) No advance payment shall be made by NCCF under any circumstances.
- 3) All payments shall be subject to applicable statutory deductions and NCCF's approved service margin.
- 4) Vendor must submit:
 1. Original GST invoice in the name of NCCF Jaipur Branch;
 2. Proof of uploading invoice on GST portal (screenshot/ARN/IRN);
 3. Bank details & PAN copy.
- 5) NCCF shall release payment within 3 working days of receiving payment from the Department, subject to verification. Payment shall be made after inspection, and acceptance of goods, subject to submission of complete documents, along with proper bill.
- 6) GST component will be released only if invoice is uploaded correctly and ITC is available.
- 7) Any denial/reversal of ITC due to vendor fault shall be recovered from the vendor's bills /security.
- 8) Final payment shall be subject to reconciliation and fulfillment of supplier's obligations.
- 9) NCCF reserves the right to deduct penalties, damages, replacement costs, or extra procurement costs due to the vendor's default.



10) NCCF reserves the right to withhold payment in case of non-compliance or defective supplies.

Tendering System:-

- Single-stage, two-bid system:
 - Technical Bid
 - Financial Bid
- Financial bids of only technically qualified bidders shall be opened.

Evaluation Criteria:-

Selection of vendor shall be made on the basis of lowest evaluated rate (inclusive of GST and transportation) and the highest service margin offered to NCCF, subject to fulfillment of eligibility criteria and technical compliance

NCCF reserves the right to distribute up to 40% of the total quantity among eligible vendors other than the L1 bidder, provided they agree to match the L1 rate and fulfill all eligibility conditions. The distribution is solely the discretion of NCCF.

Preference shall be given in the following order:

- (a) Empaneled business associates of the concerned NCCF Branch.
- (b) Empaneled business associates of other NCCF Branches.

Delivery Schedule:-

The supply must be completed within 60 days of issue of work order or as specified by NCCF/Concerned department. Delay in supply will attract liquidated damages imposed by the NCCF.

The terms, conditions, supply schedule, and technical specifications of the product shall be as finalized and adopted by NCCF for this procurement, which shall be acceptable to the bidder.

The vendor shall not assign, transfer, or sublet the work, in full or part, without prior written consent of NCCF.

In case of delay, non-supply, or rejection during inspection, the vendor shall be liable to bear the penalty and replacement costs as imposed by NCCF during that time as per the contract value.

The penalty may be upto 5% of the contract value or as deemed fit to NCCF. Any penalty or deduction imposed on NCCF by the client department due to the vendor's default shall be fully recoverable from the vendor's payment, EMD, or performance security.

Force Majeure:-

Subscribed

- Neither party shall be liable for forfeiture of performance due to causes such as natural calamity, riots, war, or any event beyond reasonable control of the parties.
- The affected party must notify the other party in writing within 7 days of such circumstances.

Arbitration:-

Disputes or differences, if any, arising under the contract, shall be referred to the arbitration of sole-arbitrator to be appointed by the mutual consent of both the parties. The arbitration proceedings shall be conducted in accordance with the Arbitration and Conciliation Act, 1996 (as amended from time to time). The venue and seat of arbitration shall be Jaipur, Rajasthan, India and the language of arbitration shall be English.

NCCF's Rights:-

NCCF reserves the right to:-

- Reject all or any bids without assigning any reason.
- To modify, suspend, change or supplement this tender at any stage. Any change to this tender document shall be uploaded on NCCF website <http://nccfindia.com>.
- In case of any ambiguity/ dispute in the interpretation of any of the clauses in this Tender Document, NCCF's interpretation of the clauses shall be final and binding on all applicants/parties.
- At any stage, if it is found that the vendor (Proprietorship, Partnership, Private Limited Company, etc) has given incorrect and misleading certificate/ information/ document(s), NCCF shall free to take suitable action including cancellation of contract, forfeiture of security / Tender security amount, blacklisting of the applicant, etc.
- All for any additional information/ documents from experienced firm (Proprietorship, Partnership, Private Limited Company, etc) and same shall be submitted by them to NCE within given time period.
- It may kindly be noted that Government of India or any State Government in India shall not be a party to this transaction.
- NCCF shall be at liberty to postpone / cancel the tender and accept or reject any bid without giving any reason whatsoever.
- NCCF shall terminate the empanelment of a Business Associate if they have competed against NCCF in this bid either individually, as a partner or in a Joint Venture.
- Violation of any terms & conditions of this tender may lead to termination/ blacklisting/ penalty.

Subletting:-

Arjun

- The vendor shall not sublet, subcontract, or assign the contract to any third party, without written consent of NCCF.
- Any attempt to subletting shall lead to termination, blacklisting and forfeiture of security amount.

Blacklisting:-

NCCF reserves the right to blacklist the agency for upto 2 years for:-

- Fraudulent documents
- Non-compliance with laws
- Corruption or unethical practices.
- Breach of confidentiality, etc.

Corrupt or Fraudulent Practices:

- It is expected that the vendors who wish to apply for this tender have highest standards of ethics.
- NCCF will reject tender if it determines that the vendor recommended for award has engaged in corrupt or fraudulent practices while competing for this tender.
- NCCF may declare a vendor ineligible, either indefinitely or for a stated duration, to be awarded or contact if it at any time determines that the vendor has engaged in corrupt and fraudulent practices during the execution of contact.

General Clause:-

- Misuse of NCCF name, logo or letter head, etc shall lead to blacklisting including forfeiture of EMD but not limited initiation of legal proceedings.

Integrity & Anti-Corruption Clause:

- The supplier shall not engage in any corrupt, fraudulent, collusive, or coercive practices. If such activities are detected, NCCF may cancel the contract immediately and may blacklist the supplier, impose penalty and take legal action as per applicable laws.

Legal & Audit Protection Clause:-

Submission of false, misleading, fabricated, or suppressed information at any stage of the tender process shall result in one or more of the following actions, at the sole discretion of NCCF:

- Rejection of the bid;
- Termination of the contract, if already awarded;
- Forfeiture of Earnest Money Deposit / Performance Security;



- Blacklisting / debarring of the bidder;
- Recovery of losses or damages suffered by NCCF;
- Initiation of appropriate legal action as per applicable laws.

Such action shall be without prejudice to NCCF's other contractual and statutory rights.

Termination for Default:-

- a) NCCF may terminate the contract, in whole or in part, by issuing a written notice to the supplier, in the event of:
 - Persistent delay in supply;
 - Repeated quality failures;
 - Breach of any term or condition;
 - Insolvency, liquidation, or cessation of business by the supplier.
- b) Termination under this clause shall be without prejudice to NCCF's right to recover losses or damages.

Termination for Convenience:

NCCF reserves the right to terminate the contract at its discretion, in whole or in part, by giving reasonable written notice, without assigning any reason and without incurring any liability, other than payment for goods duly supplied and accepted up to the date of termination.



(Onkar Chand)
Branch Manager



Vendor Declaration / Affidavit

(To be submitted on Rs.100 non-judicial stamp paper, notarized)

AFFIDAVIT

I/We, _____ having office at _____ do hereby solemnly affirm and declare as follows:

1. That I/We have read and understood the terms, conditions, technical specifications, warranty obligations, and penalty provisions of the NCCF tender no. _____ dated _____.
2. That I/We agree to supply the goods strictly in accordance with these terms and conditions and shall be fully responsible for any default, delay, or rejection attributable to us.
3. That I/We hereby undertake to indemnify and hold harmless NCCF against any financial, legal, or reputational loss arising from our non-performance, delayed supply, or quality rejection.
4. That I/We have not been blacklisted or debarred by any government department, public sector undertaking, cooperative institution, or NCCF.
5. That all documents and information submitted by us in the tender are true and correct to the best of our knowledge and belief.

DEPONENT

Verification

Verified at _____ that the contents of the above affidavit are true and correct to the best of my knowledge and belief.

DEPONENT

(Signature with Seal)



Performance Security Format

(To be submitted on Vendor's Letterhead along with DD/FDR)

PERFORMANCE SECURITY UNDERTAKING

To

The Branch Manager

National Cooperative Consumers' Federation of India Ltd. (NCCF)

Jaipur Branch

Subject: Performance Security for Tender No. _____ dated _____.

Sir,

In consideration of the NCCF having agreed to award the supply order for [Name of Work] to us, we hereby deposit a Performance Security against the total bid value (RS_) in the form of [Demand Draft/FDR No. _____ dated _____ drawn on _____ Bank] in favour of National Cooperative Consumers' Federation of India Ltd., payable at Jaipur.

We understand and agree that:

1. This Performance Security shall be valid until completion of warranty period as per the terms of both NCCF tenders
2. NCCF shall have the absolute right to forfeit this security, in full or part, for any delay, non-compliance, or quality defect attributable to us.

Yours Faithfully,

(Name and Signature of Authorised Signatory)

(Firm Name)

(Date)

(Seal)



Financial Bid Format

(To be submitted on Vendor's letterhead and signed by Authorised Signatory)

Tender No.: _____

Date: _____

Name of Work; _____

Bidder Details

S.No.	Particulars	Details
1.	Name of Firm / Company	
2.	Registered Address	
3.	GST Registration No.	
4.	PAN No.	
5.	Contact Person (Name and Designation)	
6.	Mobile No. / Email ID.	

B. Financial Quote

S.No.	Item Description	Unit	Quantity	Basic Rate	GST (%)	GST amount	Total Amount

C. Declaration by Bidder

I/We hereby declare that:

1. The above rates are inclusive of all taxes, duties, transport, installation, and warranty obligation.
2. The above rates include NCCF margin @ _____%.
3. The quoted rates shall remain firm and valid for the contract period.
4. Payment shall be released only after NCCF receives payment from the client department.
5. The selection shall be based on lowest evaluated rate and highest NCCF margin, as per tender terms.
6. All details furnished are True and correct to the best of my knowledge and belief.

Authorised Signatory: _____

Name : _____

Designation: _____




Firm Seal: _____





Date: _____




Place: _____






Annexure - IV






S.No.	Item Name	Specification	Photo	Rate per unit
1	Patient Bed with Drip Stand	1.Semi Fowler Hospital Bed with backrest elevation for patient comfort and clinical positioning. 2.ABS Head & Foot Panels: molded, impact-resistant, easy to clean and disinfect, with smooth rounded edges. 3.IV Drip Stand Provision at 4 Locations (corner sockets) for flexible IV placement from either side/end. 4.Strong MS tubular frame with powder-coated finish for corrosion resistance and long service life. 5.Bed top in CRCA sheet/perforated platform for ventilation and easy mattress support/cleaning. 6. 40 Density Mattress, 2 Section for semi fowler bed , Covered With Good Quality rexine		
2	Bed with railing	1.Semi Fowler Hospital Bed with backrest elevation for patient comfort and clinical positioning. 2.ABS Head & Foot Panels: molded, impact-resistant, easy to clean and disinfect, with smooth rounded edges. 3.IV Drip Stand Provision at 4 Locations (corner sockets) for flexible IV placement from either side/end. 4.Strong MS tubular frame with powder-coated finish for corrosion resistance and long service life. 5.Bed top in CRCA sheet/perforated platform for ventilation and easy mattress support/cleaning. 6.Bed Provided with Collapsible Rails. 7. 40 Density Mattress, 2 Section for semi fowler bed , Covered With Good Quality rexine		
3	Patient Bed Side Table (General	1.Bedside Locker Size: 16" (W) × 16" (D) × 32" (H), compact and patient-friendly design. 2.Construction: MS (mild steel) body with strong welded structure and smooth edges. 3.Storage: 1 lockable storage box (with handle) for patient belongings. 4.Finish: Epoxy powder-coated surface for corrosion resistance, easy cleaning, and long durability.		





4	ICU/ HDU Bed	<ul style="list-style-type: none"> • Overall Size: 2160 mm (L) x 1020 mm (W) x 450 mm to 810 mm (H)(without mattress). • The wired handset controls Hi-Lo Height adjustment, Trendelenburg/ Reverse Trendelenburg, Back rest and knee rest , Zero position for CPR (All Functions are Linear Actuator Based) • One touch key for flattening of bed at the lowest height for CPR on hand set. • Bed have manual emergency CPR level on both sides. Bed Top is made up of 16g Perforated mild Steel. • The bed have safety side railings , collapsible split type shall be made from ABS. The bed shall be provided with mattress. • The bed is provided with Diagonally locking 125 mm diameter wheels and diagonally lockable. Four Corner rubber buffer are fitted to the four corners of the bed. • Oxygen Cylinder holder (Detachable) is provided with the bed. The Bed have dual sided integral drainage bag rails with hooks. • All components should be thoroughly pre-treated and epoxy polyester powder Coated This finish exclude castor wheels any stainless steel parts. 		
5	Labour Table	<ul style="list-style-type: none"> • Overall approx. dimension: 1950 mm L x 675 mm W x 790 mm H (Fully extended without mattress)Strong CRCA Frame Work • Three section stainless steel table top • Backrest raised on ratchet • Middle section with perennial "U" cut • Leg section can be telescoped under the main frame • Trendelenburg and reverse Trendelenburg adjustments on screw with SS handle • Removable SS head and side railings • Complete with SS Bowl, SS Telescopic IV Rod, SS Hand grips, Padded Lithotomy Crutches (pair) and Single Step Stool (MS)Foam mattress covered with rexine 		
6	PV Table / Examination Table	<ul style="list-style-type: none"> • Overall approx. dimension: 1840 mm L x 740mmW x 810 mm H • Mild steel tubular frame work • Two section mild steel Frame with Cushioned Top • Headrest raised on ratchet • Foam mattress covered with Rexene • Legs fitted with rubber shoes • Pre-treated and powder coated finish 		
7	Attendant Bench	<ul style="list-style-type: none"> •Size: 1800mm x610mm x380mm •Attendant bed with built in cushion. •Top frame made from 50 x 25mm ERW tube. •Legs 30mm x 30 mm ERW tube with nylon feet with Castor wheels •3 horizontal supports. 		



8	Foot Step	<p>Double Foot Step (2-Step): Heavy-duty MS frame with two anti-skid steps for safe patient access. Finish & Safety: Epoxy powder-coated with anti-slip Tapeing for feet stability.</p>		
9	Officer Chairs	<p>Providing and supplying a high back chair. The seat and back shall be made of 15mm and 12mm thick hot pressed commercial plywood padded with high resilience moulded polyurethane foam 50mm thick having density 40kg/m³ in seat and 40mm thick having density 40Kg/m³ in back. The back and base of chair shall be supplied with polypropylene bead on edges and the backrest shall be made by keeping the natural curvature of the spine with full back support. The seat and back shall be arrested together with 50-60µ thick powder coated HR steel spine and the armrest shall be made black integral polypropylene arm mounted on powder coated round pipe frame completely joint with seat and back. The pedestal should be five legged injection moulded in black 30% glass filled nylon having pitch circle dia. 700 mm fitted with 5 nos. twin wheel castors. The seat size shall be 470±10 mm(W) X 460±10 mm(D) and back size shall be 460±10 mm(W) X 610±10 mm(H) from seat & overall height = 1050±10 mm.</p>		
10	Computer Table	<p>Supplying & placing computer desk of size 1200mm(W) X 600mm(D) X 750mm(H). It should have work top made up of 18mm thick PLPB with approved laminate and finish as per approved shade. The top profile shall be in rectangle shape and the edges shall be sealed with 2mm thick thin strip of impermeable PVC. The top board shall be supported on fixed pedestal at one end and fixed CPU unit at another end. The desk shall be clad with 18mm thick modesty panel which provide structural support for the desk. It should be 18mm thick pre-laminate particle board connected with both end. Key-board tray shall be provided 18mm thick pre-laminated particle board with an overall size 550mm X 350mm. The tray shall be operated by sliding channel runs on nylon roller to smooth operation. Fixed pedestal shall be provided at one side with the size 335mm X 470mm X 725mm having 3 drawer operated on sliding channel and 1 filing drawer having operated on ball bearing channel. All drawer shall be operated with SS handle with multi purpose (MP) locking mechanism. Openable storage shall be provided at another side with the size 294mm X 450mm X 725mm having one adjustment shelf to accumulate CPU. Complete understructure made in 18mm thick PLPB and 9mm for drawer base.</p>		





11	Office chair	<p>Providing and supplying a visitor chair. The seat and back shall be made of 15mm thick hot pressed commercial plywood padded with high resilience moulded polyurethane foam 50mm thick having density 40kg/m³ in seat and 40mm thick having density 32Kg/m³ in back. The same shall be upholstered with crape fabric tapestry 0.6mm thick and 235 GSM. The seat and back of chair shall be supplied with polypropylene beam on edges and the backrest shall be made by keeping the natural curvature of the spine. The seat and back shall be arrested together with 50-60µ thick powder coated HR steel spine. The armrest shall be made of black integral polypropylene arm mounted on powder coated round pipe frame completely joint with seat and back. The frame structure shall be cantilever support type made up of MS CRCA powder coated round pipe of Dia. 25.4mm with 1.6mm thick. There shall be PPCP shoe provided at the base to avoid scratches on the floor . The seat size shall be 480±10 mm(W) X 450±10 mm(D) and back size shall be 480±10 mm(W) X 400±10 mm(H) from seat & overall height = 820±10mm, overall depth = 600±10 mm.</p>		
12	Revolving Chair	<p>Providing and supplying a medium back chair. The seat and back shall be made of 15mm and 12mm thick hot pressed commercial plywood padded with high resilience moulded polyurethane foam 50mm thick having density 40kg/m³ in seat and 40mm thick having density 40Kg/m³ in back. The seat and back shall be upholstered with fabric tapestry 1mm thick and 300 GSM. The back and base of chair shall be supplied with polypropylene bead on edges and the backrest shall be made by keeping the natural curvature of the spine. The seat and back shall be arrested together with 50-60µ thick powder coated HR steel spine and the armrest shall be made of black integral polypropylene arm mounted on powder coated round pipe frame completely joint with seat and back. For seating durability the chair shall have swivel tilt 360 degree revolving mechanism with upright position locking and tilt tension adjustment which provides back strength for the chair. The pneumatic seat height adjustment for healthy seating, user can adjust seat height up to 100mm. The seat size shall be 470±10 mm(W) X 450±10 mm(D) and back size shall be 460±10 mm(W) X 380±10 mm(H) from seat & overall height = 830±10 mm.</p>		





13	Patient shifting trolley	<ul style="list-style-type: none"> •Overall approx. dimension: 2110mm Lx710mm W •Stretcher top approx. dimension: 1835 mm L x595mmW •Height adjustment by Crank mechanism: 700 mmto 970 mm (approx.) •Two section removable x-ray permeable stretchertop with sliding X-ray cassette holder •Backrest raised on ratchet •Pair of swing away type stainless steel railings •Stainless steel IV pole •Utility tray, oxygen cylinder holder and Urine bag holder •Four heavy duty castors 150 mm Dia, two with brake •Two section 40 mm thick PU foam mattress covered with rexine •Pretreated and powder coated finish 		6
14	Stretcher (Patient Shifting)	<ul style="list-style-type: none"> •Overall approx. dimension: 2030 mm L x 620 mmW x 880 mm H •Strong mild steel tubular construction •Removable MS stretcher top supported on tubular frame •Four heavy duty castors 150 mm dia, two with brake •Pretreated and powder coated finish •Mattress of 32Dn with rexine cover and 2" thickness. 		20
15	USG Benches	<p>3-Section Examination / USG Couch with backrest and leg section manually adjustable for versatile positioning. Adjustment Mechanism: Smooth ratchet-based back & leg adjustment with secure locking. Structure: Heavy-duty strong base frame (MS tubular construction) for high stability and long service life. Upholstery: 3–4 inch thick high-density foam cushion with premium, easy-to-clean, disinfectant-resistant rexine cover. Finish & Safety: Epoxy powder-coated frame with rounded edges; anti-slip feet/levelers for firm floor grip.</p>		2
16	Instrument Trolley	<p>Overall approx. dimension: 475 mm L x 610 mm W x 850 mm H Stainless steel tubular frame work Two SS shelves with three side railings on top shelf Four heavy duty castors 100 mm dia, two with brake</p>		20





17	Wheel Chair	<ul style="list-style-type: none"> • The Folding Wheelchair 24 inch Mag wheel comes equipped with swing away footrests. . • Storage pocket on rear of chairs • Powder Coated, lift able Handle • Seat Width: 16" • Overall Width: 23.50" • Overall Depth: 44" with footrests • Seat Depth: 16" • Overall Height: 36" • Weight Capacity 100kgs. 		
18	Dressing Trolley	<p>Overall approx. dimension: 1100 mm L x 460 mm W x 850 mm H Stainless steel tubular frame work Two SS shelves with three side railings on top shelf Four heavy duty castors 100 mm dia, two with brake</p>		
19	Crash Cart Trolley	<ul style="list-style-type: none"> •Overall approx. dimension: 970 mm L x 500 mm W x 1630 mm H •Stainless steel tubular framework and SS shelves. •Six removable plastic bins and two polystyrene lockable storage units with two drawers having containers of different sizes •Four heavy duty castors 125 mm dia, two with brake •Complete with four corner buffers, SS IV Rod, Cardiac massage board and Oxygen cylinder holder (MS) 		
20	Drip stand	<ul style="list-style-type: none"> •Stainless Steel tubular pipe •Four hook S.S. adjustable IV rod with a Bakelite knob •Five-legged Plastic Base Mounted on 5cm castors 		
21	Waiting hall chair (Set of 2 ss)	<p>Supplying & Placing single seater bench. The seat and back shall be made up of high quality SS perforated sheet of 1.2mm thick, pressed and welded to form the shape. The armrest shall be made up of SS . The base structure shall be supported by SS . There shall be PPCP shoe provided at the base to avoid scratches on the floor. The Seat size shall be 440±10 mm(D) X 405±10 mm(H) from ground. Overall height shall be = 755±10 mm, overall depth = 710±10 mm & overall width = 610±10 mm.</p>	 <p>Magnum 6(SS)</p>	




22	P.V. Screen	<ul style="list-style-type: none"> •Size:H 168 X W 244 cms. •Frame work made of ERW tubular pipe. •Supplied with spring wire and curtains. •Pre-treated and epoxy powder coated. 		
23	Locker (6/8 compartment)	<p>Overall size of Personal Locker Unit with add on units shall be of dimensions 380mm(W) X 450mm(D) X 1800mm(H) having 4 locker unit. Stackability shall have add - on units that can be stacked width wise to form bank of lockers having common side panel. Locking shall have cam lock with lock lever plus option. Material shall be CRCA 0.8 mm thickness. Shelf shall be uniformly distributed load capacity per each shelf level is 35 Kg maximum. Finish shall be epoxy polyester powder coated to the thickness of 50 microns. Handle/Label holder shall be aesthetically appealing Snap fit ABS plastic handle. Ventilation shall be attractive punched pattern for ventilation.</p>		
24	Open Racks	<p>Providing, placing and installing a slotted angle rack with an overall size 900mm (W) X 300mm (D) X 1800mm (H). The panel shall have 5 nos. of shelves made up of 0.8mm thick high yield strength CRCA sheet of grade 'D' confirming to IS: 513. CRCA slotted angle shall be supplied with 2mm thick having size 40mm X 40mm. All steel components shall be 40-60μ thick (DFT) powder coated after 7 tank pre-treatment process flow. Corner plate (gussets) and fasteners shall be provided for complete assembly.</p>		
25	Steel Almirah	<p>Providing, supplying and placing steel almirah. The overall size of the Almirah shall be 915mm (W) X 485mm (D) X 1980mm (H) including legs. It should be supplied with 4 nos. of adjustable shelves i.e. 5 loading compartments. All components shall be made of 0.8mm thick high yield strength CRCA sheet. Stiffeners shall be provided in shelf & door. The steel hinged door shall be provided with locking mechanism which is assembled with bolt arrangement. The shelves shall have folded constructions which have intrinsic rigidity and high load carrying capacity. Uniformly distributed load capacity per each shelf shall be 40kg maximum. The complete steel structure shall be constructed by welding and provide finishing with epoxy polyester powder coated to be thickness 50-60μ.</p>		

26	Shoe rAck	<p>Providing, supplying and placing Shoes rack (without doors). The overall size of the rack shall be 900mm (W) X 400mm (D) X 750mm (H). The cabinet shall be supplied with 3 nos. of shelf. The shelves shall have fix which have intrinsic rigidity and high load carrying capacity. Uniformly distributed load capacity of each shelf shall be 20 Kg maximum. Each rack shall be provided with stiffener at bottom for strength. The entire body panel and shelf shall be made of high yield strength 0.8mm thick CRCA sheet of grade 'D' confirming to IS: 513. The complete steel structure shall be constructed by welding and provide finishing with epoxy polyester powder coated to the thickness 40-50μ thick.</p>		
27	White Board	<p>Supply and placing of white marker board having size of 1200x900.</p>		
28	Green Board	<p>Supply and placing of green chalk board having size of 1200x900.</p>		
29	OT Table	<p>Tabletop is made with stainless steel grade. The five-section Stainless Steel tabletop is equipped with removable, antistatic mattresses. All the positions are realized by a mechanical driver. The table is furnished with a hard, robust stainless steel shell which provides the sense of dirt free & sanitized operations. Precision hydraulic system with a single lever action hydraulic life controlled by a foot pedal. Five sections stainless steel top gives anatomic adaptation to the patient body. Inbuilt Kidney Bridge and large perinea cut out for drainage. Manual floor locking system.</p>		

S.No.	Particulars	Spec.	Reference Image	Rate per unit
30	Premium Executive Table	Supplying & Placing with an overall size 2100mm X 1700mm X 750mm that is to be assembled at site. The work top shall have the size 2100mm X 900mm made up of 25mm thick PLPB with approved laminate and finish as per approved shade. The top shall be 50mm thick on edges, after 100mm from edges it should be 25mm thick. The top profile shall be in rectangle shape and the edges shall be sealed with 2mm thick thin strip of impermeable PVC. The gable end shall be made up of 50mm thick PLPB appropriate PVC edge banding. The table shall be clad with 18mm thick modesty panel of 18mm thick Pre-laminated particle board in linear shape with appropriate PVC edge banding connected with both end. The table shall have side unit for storage purpose with an overall size 750mm X 450mm X 750mm. Side Storage top shall be made up from 25mm thick prelam particle board. The side unit shall be made up of PLPB with 18mm thick like shutter, back, facia, top etc. It shall have 2 shutters. Pedestal shall be provided with an overall size 400mm X 450mm X 680mm. Laminate pedestal shall be made up of Pre-laminated particle board. The pedestal shall have 3 nos. of drawer i.e. 2 box drawer and 1 filing drawer.		
31	Executive Chair	Supplying and placing High back chair. The seat shall be made of double layered moulded (18+6)mm thick hot pressed commercial plywood upholstered with high resilience polyurethane foam (40+30)mm thick having density 40kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM and the back shall be made of double layered moulded hot pressed plywood (18+6)mm thick upholstered with high resilience polyurethane foam (30+25)mm thick having density 32kg/m ³ with black leatherite with contoured lumbar support which helps to provide full back support and maintain the natural curvature of the spine.. The seat and back shall be fixed with plywood and and the armrest shall be used metal base chrome finish cushion arm with leatherite tapestry completely joint with seat and back. The chair shall have torsion bar 360 degree revolving mechanism with upright position locking and tilt tension adjustment. The pneumatic seat height adjustment for healthy seating, user can adjust seat height upto 65mm. The seat size shall be 500±10 mm (D) X 480±10 mm (W) and back size shall be 520±10 mm (W) X700 ±10 mm (Ht) from seat. Overall height shall be = 1160±10 mm, overall depth = 700±10 mm & overall width = 65±10 mm.		
32	Computer Revolving Chair	Providing and supplying mid back chair with ergonomic design, comfortable & aesthetically appealing. The seat shall be made of 15mm thick hot pressed commercial plywood upholstered with high resilience moulded polyurethane foam 50mm thick having density 50kg/m ³ with fabric tapestry 0.6mm thick and 235 GSM and the back shall be made of metal bright bar upholstered with breathable mesh tapestry. The backrest of the chair shall be made by keeping the natural curvature of the spine with cushion base lumbar support. The seat and back shall be arrested together with 50-60µ thick powder coated HR steel spine and the armrest shall be used injection moulded polypropylene loop arm completely joint with seat. For seating durability the chair shall have push back 360 degree revolving mechanism with upright position locking and tilt tension adjustment. The pneumatic seat height adjustment for healthy seating, user can adjust seat height up to 100mm. The seat size shall be 460±10 mm(W) X 455±10 mm(D) and back size shall be 550±10 mm(H) from seat & overall height = 990±10 mm.		
33	Wooden Visitor chair	Supply and placing of peacock chair with handle and cushion in seat and back.		

34	Sofa 3 seater	<p>Supplying and placing three seater sofa that shall be constructed from 12mm thick hot pressed commercial plywood. The sofa shall be supported on MS chrome plated and the frame shall be padded with high resilience polyurethane foam having density 40Kg/m³ in seat and 32Kg/m³ in back for comfort and lumbar support. The arm shall be provided MS chrome plated round pipe having Dia. 25.4mm. The seat and back shall be upholstered with leatherite tapestry 0.8±.1mm thick and 535 GSM. The under structure shall consist of MS chrome plated round pipe frame having Dia. 25.4mm with 2mm thick. There shall be PPCP shoe provided at the bottom to avoid scratches on the floor. Overall width = 1650±10 mm, overall depth = 630±10 mm & overall height = 860±10 mm.</p>		
35	Sofa 2 seater	<p>Supplying and placing two seater sofa that shall be constructed from 12mm thick hot pressed commercial plywood. The sofa shall be supported on MS chrome plated and the frame shall be padded with high resilience polyurethane foam having density 40Kg/m³ in seat and 32Kg/m³ in back for comfort and lumbar support. The arm shall be provided MS chrome plated round pipe having Dia. 25.4mm. The seat and back shall be upholstered with leatherite tapestry 0.8±.1mm thick and 535 GSM. The under structure shall consist of MS chrome plated round pipe frame having Dia. 25.4mm with 2mm thick. There shall be PPCP shoe provided at the bottom to avoid scratches on the floor. Overall width = 1125±10 mm, overall depth = 630±10 mm & overall height = 860±10 mm.</p>		
36	Visitor Chair	<p>Providing and supplying low back visitor chair. The seat shall be made of 15mm thick hot pressed commercial plywood upholstered with high resilience polyurethane foam 40mm thick having density 40kg/m³ with fabric tapestry 0.6mm thick and 235 GSM and the back shall be made of two piece injection moulded polypropylene net cover upholstered with breathable mesh tapestry. The armrest of the chair shall be used polyurethane arm completely joint with seat & back. The frame structure shall be 4 leg type made up of MS/CRCA powder coated with round pipe of Dia. 25.4mm with 2mm thick. There shall be co-polymer polypropylene shoe provided at the base to avoid scratches on the floor. The seat size shall be 470±10 mm(W) X 460±10 mm(D) and back size shall be 460±10 mm(H) from seat & overall height = 865±10 mm.</p>		
37	Computer Table	<p>Supplying & placing computer desk of size 1200mm(W) X 600mm(D) X 750mm(H). The top board shall be supported on fixed pedestal at one end and fixed CPU unit at another end. The desk shall be clad with 18mm thick modesty panel which provide structural support for the desk. Key-board tray shall be provided. Fixed pedestal shall be provided at one side with the size 335mm X 470mm X 725mm having 3 drawer operated on sliding channel and 1 filing drawer having operated on ball bearing channel. All drawer shall be operated with SS handle with multi purpose (MP) locking mechanism. Openable storage shall be provided at another side with the size 294mm X 450mm X 725mm having one adjustment shelf to accumulate CPU. Complete understructure made in 18mm thick Pre-laminated particle board with appropriate edge banding and drawer base shall be 9mm thick.</p>		

38	Revolving Chair medium Back	<p>Providing and supplying a medium back chair with ergonomic design, comfortable & aesthetically appealing. The seat and back shall be made of 15mm and 12mm thick hot pressed commercial plywood padded with high resilience moulded polyurethane foam 50mm thick having density 40kg/m³ in seat and 40mm thick having density 40Kg/m³ in back. The seat and back shall be upholstered with fabric tapestry 1mm thick and 300 GSM. The back and base of chair shall be supplied with polypropylene bead on edges and the backrest shall be made by keeping the natural curvature of the spine. The seat and back shall be arrested together with 50-60µ thick powder coated HR steel spine and the armrest shall be made of black integral polypropylene arm mounted on powder coated round pipe frame completely joint with seat and back. The pneumatic seat height adjustment for healthy seating, user can adjust seat height up to 100mm. The seat size shall be 470±10 mm(W) X 450±10 mm(D) and back size shall be 460±10 mm(W) X 380±10 mm(H) from seat & overall height = 830±10 mm.</p>		
39	Office Table	<p>Supplying & Placing Computer Desk of size 1500mm(W) X 750mm(D) X 750mm(H). It should have work top made up of 25mm thick PLPB. The top shall be supported on fixed pedestal at one end and fixed CPU unit at another end. The desk shall be clad with 18mm thick modesty panel which provide structural support for the desk. At one side a fixed pedestal shall be provided with the size 400mm X 620mm X 725mm with 3 drawer. The drawer shall be operated on roller channel and ball bearing channel to enable smooth operation. The drawer shall be operated with SS handle and multi-purpose (MP) locking mechanism. Other side of table fixed pedestal shall be provided with the size 400mm X 600mm X 725mm having one adjustment shelf to accumulate CPU. It shall have one shutter operated with SS handle and concealed crank hinge. Complete understructure made in 18mm thick Pre-laminated particle board with appropriate edge banding and drawer base shall be 9mm thick.</p>		
40	Visitor Chair	<p>Providing and supplying low back visitor chair. The seat shall be made of 15mm thick hot pressed commercial plywood upholstered with high resilience polyurethane foam 40mm thick having density 40kg/m³ with fabric tapestry 0.6mm thick and 235 GSM and the back shall be made of two piece injection moulded polypropylene net cover upholstered with breathable mesh tapestry. The armrest of the chair shall be used polyurethane arm completely joint with seat & back. The frame structure shall be 4 leg type made up of MS/CRCA powder coated with round pipe of Dia. 25.4mm with 2mm thick. There shall be co-polymer polypropylene shoe provided at the base to avoid scratches on the floor. The seat size shall be 470±10 mm(W) X 460±10 mm(D) and back size shall be 460±10 mm(H) from seat & overall height = 865±10 mm.</p>		
41	Lab Stool	<p>Overall Dimension: Overall Sizes Diagonal Leg Dia 538 mm H510 min-690max. Top plate made of SS 304 made sheet with spin section of thickness 1mm & non corrosive. It has a diameter of 305mm, seat base made of MS ring and rectangular tube. EN8 Screw having dia of 22 mm is used for height adjustment of the seat base. The round hub made of MS ERW tube having dia of 38mm and thickness 2 mm. The Hub is welded with the legs and it accommodate and cover the lead screw mechanism. The under-structure consist of 4 legs made up of MS ERW tube of diameter 25.4 mm and 1.6mm thick. The press formed pipe leg give a round & clean look. All the legs is Provided with 4 nos of Nylon-6 bush. All metal components are pre treated with zinc phosphating in 7 tank process and then powder coated with epoxy polyester powder coating. Safe working load is 135kg</p>		

42	Almirah Big	<p>Providing, supplying and placing steel almirah in perfectly upright and straight position. The overall size of the Almirah shall be 915mm (W) X 485mm (D) X 1980mm (H) including legs. It should be supplied with 4 nos. of adjustable shelves i.e. 5 loading compartments. All components shall be made of 0.8mm thick high yield strength CRCA sheet. Stiffeners shall be provided in shelf & door. The steel hinged door shall be provided with locking mechanism which is assembled with bolt arrangement. The shelves shall have folded constructions which have intrinsic rigidity and high load carrying capacity. Uniformly distributed load capacity per each shelf shall be 40kg maximum. The complete steel structure shall be constructed by welding and provide finishing with epoxy polyester powder coated to be thickness 50-60μ.</p>		
43	Writing Chair	<p>Providing and supplying student chair with desklet. The seat and back shall be made up of hot pressed commercial plywood and one piece injection moulded 20% glass filled polypropylene padded with high resilience polyurethane foam having density 45Kg/m³ in seat and 32Kg/m³ in back. The same shall be upholstered with fabric tapestry. The seat and back shall be arrested together with metal pipe frame. The chair shall be supplied with foldable writing pad 10mm thick made up of polypropylene shell mounted on metal pipe frame having cross-section area 30X15mm 1.6mm thick. The structure shall be supported on MS/CRCA pipe frame having cross-section area 30X15X1.6mm and the under-structure shall consist of four legs made up of CRCA reducing pipe having dia. 25.4mm with 1.6mm thick. The complete steel structure shall be epoxy powder coated to 40-60μ dry film thickness. The seat size shall be 470±10 mm(W) X 465±10 mm(D), back size shall be 450±10 mm(W) X 385±10 mm(H) from seat. Overall height shall be 790±10 mm.</p>		
44	3 seater Chair Set	<p>Supplying & Placing three seater bench. The seat and back shall be made of high quality cold rolled MS perforated sheet of 1.2mm thick, pressed and welded to form the shape. The seat and back electrostatically coated with epoxy powder and then cured under heat to allow it to form a skin. The armrest shall be made up of mild steel powder coated with 1.2mm thick sheet. The base structure shall be supported by MS powder coated with 50-60μ (DFT). There shall be PPCP shoe provided at the base to avoid scratches on the floor. Overall height shall be = 755±10 mm, overall depth = 710±10 mm & overall width = 1675±10 mm.</p>		
45	Examination Table with Mattress	<p>Supply and placing of examination couch having overall size of 1880x610x850 with mattress. The complete structure to be made in MS CR sheet and finished with powder coating of approved shade.</p>	